Thermischer Strömungssensor FS7 für Gase



Durchflussbereich von 0 bis 100 m/s, -20 °C bis +150 °C

Zur Messung von Durchflussraten mit symmetrischem Heizelementdesign und ausgezeichneter Empfindlichkeit und Reproduzierbarkeit. Dieser Allrounder zeichnet sich durch Langzeitstabilität und Reproduzierbarkeit aus.

Product Name: FS7.0.1L.195
Medium: Gasströmung
Strömungsrichtung: Eine Richtung (anemometrisch)
Betriebstemperaturbereich: -20 °C bis +150 °C
Chipgrösse/Abmessungen: 6.9 x 2.4 x 0.20 mm
Anschluss: Cu/Ag-Litzen, PTFE-isoliert
Drahtlänge: 195 mm
Flow range CTA mode: 0/ms bis 100 m/s
Ansprechzeit T63: ~200 ms (Sprung von 0 auf 10000 sccm)
Sensitivität: 0.01 m/s

Substrat: Keramik
Draht: 3 pins, Cu/Ag-stranded wires, PTFE insulated
Product Old code: 050.00216
Product code: 103705

Product details

Product description FS7

The IST AG FS7 thermal mass flow sensors are the successors of the FS5 flow sensors and exhibit a symmetrical heater design and enhanced sensitivity. The FS7 flow sensor is applicable in gas and offer excellent long-term stability. The small thermal mass of the FS7 sensor provides a fast response time. Additionally, the standard FS7 sensor is also available with a housing which is easily implemented into various applications.

The IST AG FS7 flow sensors are optimal for measuring gas flow in various flow applications.

Benefits & Characteristics of the FS7 gas flow sensor

- Easy adaptation in various applications and housings
- Excellent long-term stability
- Simple signal processing
- Simple calibration
- Stable platinum technology
- Excellent reproducibility

Customer-specific sensor available upon request.

The online shop

Quantity (pieces)	Price (per piece)
5-49	CHF 28.60
50-99	CHF 22.70
100-150	CHF 20.09

Lager: **82**