


Pt100 (202) class F0.1 with Ni/Au wires



Thin-film platinum 100 Ohm RTD component

Platinum temperature sensor with gold coated nickel wires

Product Name: POK1.202.3K.Y.020 Nominal resistance: 100Ω at 0 °C Operating temperature range: $-200 \degree$ C to $+300 \degree$ C TCR: Pt 3850 ppm/K Chip size/dimensions: $2.0 \times 2.0 \times 1.3 \text{ mm}$ Tolerance/class: IEC 60751 F0.1 (IST tolerance class Y) Connection type: Ni/Au-wire, Ø 0.2 mm (only < 600 °C) Wire length: 20 mm Packaging: Blister Product code: 101607

Product details

Platinum Sensors

Innovative Sensor Technology IST AG platinum temperature sensors provide solutions for extreme temperature applications and are designed with the highest quality materials, allowing them to operate within a wide temperature range of -200 °C to +1000 °C. Standard IEC 60751 sensors are offered in class F0.3 (0.12 %), class F0.15 (0.06 %), F0.1 (0.04 %), and higher accuracies upon request.Our sensors are available in wireless (SMD) and wired configurations, and in sizes ranging from 0.75 mm to 10 mm (L), and 0.75 mm to 5.08 mm (W). Standard sensors can be customized with a variety of lead wire material, insulations, length, and configurations.

With many years of experience, IST AG also offers development of customer-specific applications in terms of sensor technology development and consultation. As part of the standard development process, IST AG offers support at the point of implementation - this way we ensure the best sensor solution for specific applications.

More information on platinum temperature sensors

Quality

Consistent with the well-known, high-quality standards in Switzerland, IST AG is certified according to ISO 9001:2015 (quality) and ISO 14001:2015 (environment). Appropriate processes are part of our daily work. They are regularly audited and extended parallel to the growth of our company.

> Read more

The online shop

Quantity (pieces) Price (per piece)

1-49	CHF 4.84
50-99	CHF 3.84
100-150	CHF 3.40

Stock: **351**