

## Flow sensor FS7.4W



Gas flow sensor with flow range from 0 to 100 m/s and temperature range from -20 °C to +400 °C

For measuring flow rates using a symmetrical heater design and having an excellent sensitivity and reproducibility.

**Product Name:** FS7.0.4W.015

**Measured medium:** Gas Flow

**Flow direction:** One direction (anemometric)

**Operating temperature range:** -20 °C to +400 °C

**Chip size/dimensions:** 6.9 x 2.4 x 0.20/0.60 mm

**Connection type:** Pt/Ni wires

**Flow range CTA mode:** 0/ms to 100 m/s

**Response time t63:** ~200 ms (jump from 0 to 10000 sccm)

**Response sensitivity:** 0.01 m/s

**Substrate:** Ceramic

**Sensor wire:** 3 pins, Pt/Ni-wires, Ø 0.2 mm, 15 mm long

**Product Old code:** 350.00218

**Product code:** 104999

## Product details

### Product description FS7.4W

The IST AG FS7.4W gas flow sensor has been developed for applications with temperatures up to 400 °C. The design of the FS7.4W is based on the FS7 design which offers a symmetrical heater that enhances sensitivity. The FS7.4W flow sensor is applicable in gas and offers excellent long-term stability. The small thermal mass of the FS7.4W sensor provides a fast response time.

### Benefits & Characteristics of the FS7 gas flow sensor

- Easy adaptation in various applications and housings
- Excellent long-term stability
- Simple signal processing
- Simple calibration
- Stable platinum technology
- Excellent reproducibility

[Customer-specific sensor available upon request.](#)

### The online shop

Quantity (pieces)	Price (per piece)
-------------------	-------------------

5-49	CHF 24.57
------	-----------

50-99	CHF 22.04
-------	-----------

100-150	CHF 19.50
---------	-----------

Склад: **318**