

physical. chemical. biological.











# P0K1.202.6W.B.010


## Platinum sensor with wires, ESD-optimized For high temperatures

#### Benefits & Characteristics

- Excellent long-term stability
- Low self-heating
- Fast response time

- Vibration and temperature shock resistant
- ESD-optimized design

#### Illustration<sup>1)</sup>



#### Technical Data

Operating temperature range:	-200 °C to +600 °C
Nominal resistance:	100 Ω at 0 °C
Characteristics curve:	3850 ppm/K
Long-term stability:	< 0.04 % at 1000 h at maximal operating temperature
Tolerance class (dependent on temperature range):	IEC 60751 F0.3 B (IST AG reference)
Connection:	Pt-cladded Ni-wire, $\emptyset$ 0.2 mm (solderable, weldable, crimpable, brazeable), 10 mm long
Dimensions L x W x H / H2:	1.8 x 2.0 x 0.65 / 1.3 mm
Tolerance (chip):	L $\pm 0.2$ mm, W $\pm 0.2$ mm,H $\pm 0.1$ mm, H2 $\pm 0.3$ mm
Special:	ESD-optimized acc IEC/EN 61000-4-2

### Product Photo



P0K1.202.6W.B.010\_155764 1/2



physical. chemical. biological.











#### Order Information

Description: Order code: Former main reference P0K1.202.6W.B.010 155764 100871

#### Additional Documents

	Document name:
Application Note:	ATP_E



P0K1.202.6W.B.010\_155764